



6390 Philips Highway
 Jacksonville, FL 32216
 Phone (904) 737-7144

SPECIFICATION DATA SHEET

MODEL No. 1298-FL

SLANTED DUCT BOARD BOX, R-6.0

Date: 03/11/10 rev.

Drawn by: DON.JR.

DIMENSIONAL DATA

OUTER BOX DIMENSION IS 3" GREATER THAN REGISTER DIMENSION.


REGISTER DIMENSION	"A" DIMENSION
8"x4", 10"x4", 12"x4", 14"x4"	8"
6"x6", 8"x6", 10"x6", 12"x6", 14"x6"	9-1/2"
8"x8", 10"x8", 12"x8", 14"x8"	11"
10"x10", 12"x10"	12-1/2"
12"x12"	14"
14"x14"	15-1/2"

FABRICATION DATA

OUTER FRAME FABRICATED FROM 30 GAUGE GALVANIZED STEEL.
 DUCT BOARD TOP AND SIDES.

FEATURES

R-6.0 INSULATION.
 SOLID CORNERS WITH HANGER HOLES.
 1/2" DRYWALL FLANGE.
 HOLE CLUSTER FOR REGISTER ATTACHMENT.
 SLANTED DUCT BOARD TOP ALLOWS FOR VARIOUS COLLAR INLET SIZES.
 BLACK INTERIOR.



OPTIONS

No. 1298 SLANTED DUCT BOARD BOX, R-4.2 INSULATION, BLACK INTERIOR.

SPECIAL NOTES

INTERNAL INSULATION USED MEETS THE REQUIREMENTS OF ASTM C 1338 (FORMERLY ASTM C 665) STANDARD TEST METHOD FOR FUNGI RESISTANCE.